

Vertical Laminar Flow Cabinet

——Double Sides Type



LED Display
Microprocessor control system, LED display.



UV Lamp
Emission of 253.7 nanometers for most efficient decontamination.



Double Sides
Double sides work bench, operators can sit face to face.

TECHNICAL PARAMETERS

Model	BBS-DSC	BBS-SSC
External Size (W*D*H)	1040*630*1730mm	1440*630*1730mm
Internal Size (W*D*H)	940*630*540mm	1340*630*540mm
Work Surface Height	730mm	
Display	LED Display	
Airflow Velocity	Average of 0.3~0.5m/s	
Material	Main Body: Cold-rolled steel with anti-bacteria powder coating Work Table: 304 stainless steel	
Pre-filter	Polyester fiber, washable	
HEPA Filter	99.999% efficiency at 0.3um	
Noise	<60dB	
Front Window	Manual, 5mm toughened glass, anti-UV	
Max Opening	350mm	350mm
UV Lamp	Emission of 253.7 nanometers	
Fluorescent Lamp	21W*1	28W*1
Consumption	350W	600W
Caster	Universal caster with leveling feet	
Power Supply	110/220V±10%; 60/50Hz	
Standard Accessory	Fluorescent lamp, UV lamp*2, Base stand	
Gross Weight	200kg	260kg
Package Size (W*D*H)	1200*830*1350mm	1600*830*1350mm